



Driving Your Vision

A division of Endicott Research Group, Inc.

GEN24WUV12V

**Constant Voltage, 24W, 0 - 2A,
Non-Dimmable**

2601 Wayne Street, Endicott, NY 13760 • www.ERGLighting.com • 1-800-215-5866



Description

Driver Type: Constant Voltage	Total Output Power: 24W
Input Voltage Range: 120~277Vac +/- 10%	Selectable Outputs: 1
Dimming: Non-Dimming	Warranty: 5 years
Certifications: UL8750; UL879 IP20 dry/damp	Protections: temperature; current; short circuit

Applications

Signage • High Bay

Performance Specifications

Model Number	Max Output Power	Output Current	Output Voltage	Efficiency	Remote Mounting Distance (#18AWG)	Class 2	
						US	Canada
GEN24WUV12V	24W	0 - 2A	12V	80%	19 ft.	✓	✓

ELECTRICAL SPECIFICATIONS:		ENVIRONMENTAL SPECIFICATIONS/ SAFETY AND EMC COMPLIANCE:	
Input Voltage Range:	120~277Vac ± 10%	Operating Temperature:	-30 to 60°C
Frequency:	50/60Hz	Storage Temperature:	-40 to 85°C
Power Factor:	>0.9 @full load	Humidity:	5% to 95%
Inrush Current:	7A @230V	MTBF:	376,000 hours at 40°C ambient (~70°C Case temp)
Max Input Current:	0.27A @120V	Maximum Case Temperature:	90°C
THD:	<20%	UL/cUL	UL 8750 and UL879
Protection:	Over Temperature, Over Current, and Short Circuit	FCC, 47CFR Part 15	Class B Consumer Limit
Withstand Voltage:	I/P – O/P 2k Vac	EN61000-3-2	

GEN24WUV12V

**Constant Voltage, 24W, 0 - 2A,
Non-Dimmable**

2601 Wayne Street, Endicott, NY 13760 • www.ERGLighting.com • 1-800-215-5866

PHYSICAL DIMENSIONS:	
Length (L):	4.80"
Width (W):	1.58"
Height (H):	0.96"
Mounting (M):	4.29"
Weight:	0.22 kg
WIRE SPECIFICATIONS:	
Input:	12", UL 1316 #18AWG (Black and White)
Output:	12", UL 1316 #18AWG (Red and Blue)

WIRING DIAGRAM	LIFETIME vs CASE TEMPERATURE:																
	<table border="1"> <caption>Lifetime vs Case Temperature Data</caption> <thead> <tr> <th>Case Temperature (°C)</th> <th>Lifetime (khrs)</th> </tr> </thead> <tbody> <tr><td>30</td><td>100</td></tr> <tr><td>40</td><td>100</td></tr> <tr><td>50</td><td>100</td></tr> <tr><td>60</td><td>85</td></tr> <tr><td>70</td><td>60</td></tr> <tr><td>80</td><td>40</td></tr> <tr><td>90</td><td>20</td></tr> </tbody> </table>	Case Temperature (°C)	Lifetime (khrs)	30	100	40	100	50	100	60	85	70	60	80	40	90	20
Case Temperature (°C)	Lifetime (khrs)																
30	100																
40	100																
50	100																
60	85																
70	60																
80	40																
90	20																